

## PRODUCT DATA SHEET

## OMEGA SUB Screed Sheeting

Is a high vapour-impermeable moisture and radon barrier. The special multi-layer sheeting consists of a quality corrosion-resistant aluminium layer with fleece reinforcement on both sides. The sheeting was specially developed as damp-proofing for use on floor slabs with ground contact as a protection against ascending moisture in accordance with DIN 18195-4 or on intermediate floors, as vapour barrier above rooms which are subject to a high degree of stress in terms of construction physics. The adhesive backing on both sides permits a quick, clean and tight seam during handling.

### FIELD OF APPLICATION

- seal on floor slabs with ground contact (DIN 18195-4) against ground moisture
- concrete floor against residual moisture
- intermediate floor as vapour barrier
- radon barrier
- vapour barrier below non-ventilated roof insulation

### ADVANTAGES

- highly flexible
- resistant to perforation
- alkali-resistant
- vapour impermeable
- water-tight
- radon-tight
- optional floor covering

### RECOMMENDED PRODUCTS



AIRSTOP ELASTO Adhesive Tape



AIRSTOP SOLO Adhesive Tape








AIRSTOP FROZEN Adhesive Paste

### AVAILABLE IN THE FOLLOWING DIMENSIONS

Roll width	1,5 m
Roll length	25 m
Roll area	37,5 m <sup>2</sup>

### PRODUCT DATA

Material composition	synthetic with elastomer strips	
Thickness	0,5 mm	
Weight	200 g/m <sup>2</sup>	
sd-value	1500 m	
Temperature resistance - Standard	-30 °C - 80 °C	
Resistance to water flow	W1	
Expandability EN 12311-1	 25 %	 18 %
Tensile strength - Standard EN 12311 - 1	 200 N/50 mm	 160 N/50 mm
Tear propagation resistance - Standard EN 12310-1	 50 N	 50N

# OMEGA SUB Screed Sheeting

## INFO

The sheeting is laid loosely with approx. 10 cm overlap on even ground surfaces which are free from sharp edges and soiling.

If required the membrane can be bonded with the substrate over the entire surface using UNI XL Primer Spray (contact bonding method).

On rising structural elements, the sheeting must be lifted up to the upper edge of the finished floor. The longitudinal seams become permanently sealed and watertight by simply pulling off the backing strips followed immediately by pressing down the adhesive joint.

End joints and seams must have an overlap of min. 10 cm, using AIRSTOP ELASTO Adhesive Tape.

Membrane connections at penetration points, rising structural elements and damp-proof courses must be made using AIRSTOP ELASTO Adhesive Tape. The overlap should be min. 10 cm. If required the substrate may be pre-treated using UNI Primer Spray.



### ISOCELL GmbH & Co KG

Gewerbestraße 9  
5202 NEUMARKT AM WALLERSEE | Österreich  
Tel.: +43 6216 4108 | Fax: +43 6216 7979  
office@isocell.at

### ISOCELL SCHWEIZ AG

Herbergstrasse 29  
9524 Zuzwil | Suisse /Schweiz  
Tel.: +41 71 940 06 72  
office@isocell.ch

### ISOCELL FRANCE

170 Rue Jean Monnet | ZAC de Prat Pip Sud  
29490 GUIPAVAS | France  
Tél.: +33 2 98 42 11 00 | Fax: +33 2 98 42 11 99  
contact@isocell-france.fr

### ISOCELL BUREEL BELGIË

Außenborner Weg 1 | Schoppen  
4770 Amel | Belgique  
Tel.: +32 80 39 90 58 | Fax: +32 80 39 97 68  
office@isocell.be

### ISOCELL Sverige AB

Köpsvängen 10  
168 67 BROMMA | Sverige  
Tel.: +46 10 130 25 00  
info@isocell.se

**ISOCELL**  
[www.isocell.com](http://www.isocell.com)